



11511

| REF | PART NO. | QTY | DESCRIPTION | SEE SEC. | NOTES |
|-----|----------|-----|------------------|----------|---|
| 1 | 860027 | 2 | Engine bracket | | FRONT. WITH HOLE FOR M16 ADJUSTING BOLT |
| | 860953 | 2 | Engine bracket | | FRONT. WITH HOLE FOR M18 ADJUSTING BOLT |
| 2 | 965192 | 6 | Flange screw | | L = 40 MM |
| | 965193 | 2 | Screw | | L = 50 MM |
| 3 | 940280 | 8 | Spring washer | | |
| 4 | 859375 | 1 | Engine bracket | | P. REAR. WITH HOLE FOR M16 ADJUSTING BOLT |
| | 860952 | 1 | Engine bracket | | P. REAR. WITH HOLE FOR M18 ADJUSTING BOLT |
| | 859376 | 1 | Engine bracket | | S.B. REAR. WITH HOLE FOR M16 ADJUSTING BOLT |
| | 860954 | 1 | Engine bracket | | S.B. REAR. WITH HOLE FOR M18 ADJUSTING BOLT |
| 5 | 940280 | 4 | Spring washer | | |
| | 955897 | 2 | Washer | | |
| 6 | 966343 | 3 | Screw | | L = 35 MM S.B |
| | 966343 | 1 | Screw | | L = 35 MM P |
| | 965226 | 2 | Flange screw | | L = 45 MM P |
| 7 | 846764 | 4 | Rubber element | | WITH M16 ADJUSTING BOLT |
| | | | Bulletin 44-26 | 44-26-EN | Reinforced Rubber Cushion |
| 7 | 876598 | 4 | Rubber element | | WITH M18 ADJUSTING BOLT |
| 8 | 955900 | 4 | · Washer | | |
| 8A | 846768 | 4 | · Adjuster screw | | M16 |
| | 860950 | 4 | · Adjuster screw | | M18 |
| 9 | 955805 | 8 | Nut | | M16 |
| | 955806 | 8 | Nut | | M18 |
| 10 | 191940 | 6 | Washer | | D = 40 MM. FOR M16 ADJUSTING BOLT |
| | 955900 | 2 | Washer | | D = 50 MM. FOR M16 ADJUSTING BOLT |
| | 955901 | 4 | Washer | | D = 34 MM. FOR M18 ADJUSTING BOLT |
| | 978991 | 4 | Washer | | D = 40 MM. FOR M18 ADJUSTING BOLT |
| 11 | 941912 | 4 | Spring washer | | FOR M16 ADJUSTING BOLT |
| | 941913 | 4 | Spring washer | | FOR M18 ADJUSTING BOLT |