



REF	PART NO.	QTY	DESCRIPTION	NOTES
1	832720	1		RATIO 1,61:1. INCLUDED IN COMPLETE DRIVE UNIT
2	832722	1	• Bearing housing	
3	875433	1	• Gear housing	
4	832580	1	• • Exhaust outlet	
5	959450	1	• • Screw	
6	183497	1	• • Needle bearing	
7		1	• • • WASHER	
8	941812	2	• • Screw	
9	832555	1	• Countershaft	
10	183374	1	• Ball bearing	
11	941832	X	• Adjusting washer	TH = 0,05 MM
	941833	X	• Adjusting washer	TH = 0,20 MM
12	875440	1	• Driveshaft	
13	183390	1	• • Needle bearing	
14	11072	1	• Roller bearing	
15	897387	1	• Spacer ring	
16	907023	1	• Lock washer	IK
17	906633	1	• Nut	
18	814164	1	• Flange nut	
19	814165	1	• Washer	IK
20	181366	1	• Ball bearing	
21	907025	1	• Lock washer	IK
22	906635	1	• Round nut	
23	832624	1	• Gear set	RATIO 1,61:1
24	914474	1	• Lock ring	
25	814482	1	• Oil pump screen	
26	832548	1	• Pump rotor	
27	832725	1	• Washer	
28	953449	6	• Stud	
29	955825	6	• Nut	
30	925261	2	• O-ring	IK
31	875805	1	• Zinc ring kit	(832524)
32	940203	2	• • Screw	
33	897426	2	• Sealing ring	IK
34	839534	1	• Line cutter	
35		1	• PROPELLER CONE	REPLACED BY 875495.
	850785	1	• Propeller cone	
35A	851261	1	• Washer	REPLACED BY 1EA 839027 1EA 875495.
36	897367	1	• Washer	
37	804262	1	• Plug	PZ-2785179
	839354	1	• Plug	PZ2785180-
38	804261	1	• Gasket	PZ-2785179
	955974	1	• O-ring	PZ2785180-
40	944522	X	• Shim	TH = 0,05 MM
	42981	X	• Shim	TH = 0,10 MM
	42980	X	• Shim	TH = 0,20 MM
41	944970	X	• Adjusting washer	TH = 1,60 MM
42	944561	X	• Adjusting washer	TH = 0,05 MM
	944562	X	• Adjusting washer	TH = 0,10 MM
	851767	X	• Adjusting washer	TH = 0,20 MM
43	832191	1	• Gasket	IK
44	925256	1	• O-ring	IK
45	875183	1	Splined sleeve	
46	914508	1	• Snap ring	
47	941810	4	Screw	