



REF	PART NO.	QTY	DESCRIPTION	SEE SEC.	NOTES
1	839449	1			P2-2793195. REPLACED BY 1EA 814598 1EA 814601 1EA 814603.
	850460	1	Upper gear unit		P2-2898014. REPLACED BY 832120.. REPLACED BY 1EA 814598 1EA 814601 1EA 814603.
	851340	1	Upper gear unit		P22898015-. REPLACED BY 850788.
2	832674	1	· Housing		
3	941814	2	· Stud	04C-0600	
4	832667	1	· Gear housing cover		
5	804342	1	· · Screw		EARLY TYPE
6	804344	1	· · Gasket	IK	EARLY TYPE
7	814179	1	· Plug		LATE TYPE
8	897682	1	· Gasket	IK	LATE TYPE
9	941807	3	· Screw		
10	814643	1	· Hollow screw		
11	955989	1	· O-ring	IK	
12	832669	1	· Gasket	IK	
13		1	· GEAR SET		PZ-2721098. OPPOSITE REVOLUTION IN RELATION TO ENGINE.
	839027	1	· Drive gear set		PZ2721099-
14	875425	1	· Bearing box		
15	951940	1	· · Tensioning din		
16	183247	1	· · Bearing		
17	183668	1	· · Roller bearing		
18	897772	1	· · Oil deflector		
19	925256	2	· O-ring	IK	
20	941826	X	· Adjusting washer		TH = 0,5 MM
	941827	X	· Adjusting washer		TH = 0,20 MM
	948230	X	· Shim		TH = 0,35 MM
21	839253	1	· Sealing ring	IK	
22	914538	1	· Lock ring		
23	832675	1	· Washer		
24	956000	1	· O-ring	IK	
25	943871	X	· Shim		TH = 0,05 MM
	943872	X	· Shim		TH = 0,10 MM
	943873	X	· Shim		TH = 0,20 MM
26	832730	1	· Joint		PZ-2721098
	839028	1	· Joint		PZ2721099-
			· Bulletin P-44-1-5	P-44-1-5-EN	U-joints
27	897774	1	· · Joint fork		
			· · Bulletin P-44-1-5	P-44-1-5-EN	U-joints
28	832680	1	· · Joint fork		PZ-2721098
	839026	1	· · Steering yoke		PZ2721099-
29	897706	1	· · Intermediate section		
30	897707	2	· · Cross piece		
31	897776	4	· · · Lock ring		
32		8	· · · NEEDLE BEARING		
33		8	· · · PROTECTOR RING		
34		8	· · · CORK RING		
35		1	· BOLT		PZ-2721098. REPLACED BY 832121.
	851293	1	· Screw		PZ2721099- (945090)
36	832771	1	· Washer		PZ-2721098
	839013	1	· Washer		PZ2721099-
37	832573	1	· Clamping ring		PZ-2793195
	839589	1	· Clamping ring		PZ-2898014
	851265	1	· Clamping ring		P22898015-
37A	852705	1	· Pivot pin		(851263) P22898015- REPL BY 852705
37B	941807	2	· Screw		P22898015-
38	956590	4	· Screw		
39	942598	4	· Washer		
40	183457	2	· Ball bearing		
	183729	2	· Bearing		REPLACED BY 1EA 850356, 1EA 839592.
41	832644	2	· Bearing sleeve		
42	943869	X	· Adjusting washer		TH = 0,05 MM

REF	PART NO.	QTY	DESCRIPTION	SEE SEC.	NOTES
42	946179	X	· Adjusting washer		TH = 0,10 MM
	943870	X	· Adjusting washer		TH = 0,20 MM
43	943866	X	· Adjusting washer		TH = 0,10 MM
	943867	X	· Adjusting washer		TH = 0,20 MM
	943868	X	· Adjusting washer		TH = 0,40 MM
44	897385	1	· Shaft		
45	814601	1	· Sliding sleeve		
			· Bulletin P-44-1-8	P-44-1-8-EN	Shift mechanism, shift cone and shoe
46	813970	1	· Spring		
47	26411	1	· Spacer		
48	914459	1	· Lock ring		REPLACED BY 1EA 851316, 1EA 851267.
	951077	1	· Lock ring		PZ-2793195.
49	181359	4	· Needle bearing		
50	897308	2	· Spacer ring		
51	897313	1	· Spacer ring		
52	897312	2	· Lock ring		
53	839332	1	· Nut		TH = 2,00 MM ALT
	839333	1	· Nut		TH = 2,37 MM ALT
	839334	1	· Nut		TH = 2,65 MM ALT
54	839504	1	· Shift mechanism		
55	839505	1	· · Bearing housing		
56	897816	1	· · Eccentric piston		
			· · Bulletin P-44-1-7	P-44-1-7-EN	Shift mechanism, eccentric piston
57	814603	1	· · Dog		
58	814184	1	· · Spring		
59	60309	2	· · Ball		EARLY TYPE
60	839136	2	· · Spring		EARLY TYPE
61	941338	X	· · Locking wire	IK	EARLY TYPE L = 300 MM
62	897711	1	· · Screw		
63	897871	X	· · Adjusting washer		TH = 0,20 MM
64	958838	1	· · Sealing ring	IK	(941866)
65	951924	1	· · Tensioning din		
66	942871	1	· · Pin		
67	925093	1	· · O-ring		
68	940169	4	· Screw		
69	875256	1	· Rubber bellows		
70	961677	1	· Clamp		
71	961676	1	· Hose clamp		
72	839351	1	· Oil dipstick		
73	804261	1	· Gasket	IK	PZ-2785179
	955974	1	· O-ring	IK	PZ2785180-
74	814687	1	· Sign		
75	804269	2	· Drive screw		
76	832716	1	Shoulder screw		PZ-2793195 1/2"
	839696	1	Shoulder screw		P2-2898014 M18
77	832570	1	Cover		
78	897873	1	· Latch		
79	943218	1	· Screw		
80	941816	1	Screw		
81	832726	1	Sign		