



DRIVE 270

| REF | PART NO. | QTY | DESCRIPTION | NOTES |
|-----|----------|-----|--------------------|--|
| 1 | 832701 | 1 | Gear under | RATIO.2,15:1. REPLACED BY 850788. |
| 2 | 832722 | 1 | • Bearing housing | |
| 3 | 875433 | 1 | • Gear housing | |
| 4 | 832580 | 1 | • • Exhaust outlet | |
| 5 | 959450 | 1 | • • Screw | |
| 6 | 183497 | 1 | • • Needle bearing | |
| 7 | | 1 | • • • WASHER | |
| 8 | 941812 | 2 | • • Screw | |
| 9 | 832555 | 1 | • Countershaft | |
| 10 | 183374 | 1 | • Ball bearing | |
| 11 | 941832 | X | • Adjusting washer | TH = 0,05 MM |
| | 941833 | X | • Adjusting washer | TH = 0,20 MM |
| 12 | 875440 | 1 | • Driveshaft | |
| 13 | 183390 | 1 | • • Needle bearing | |
| 14 | 11072 | 1 | • Roller bearing | |
| 15 | 897387 | 1 | • Spacer ring | |
| 16 | 907023 | 1 | • Lock washer | IK |
| 17 | 906633 | 1 | • Nut | |
| 18 | 814164 | 1 | • Flange nut | |
| 19 | 814165 | 1 | • Washer | IK |
| 20 | 181366 | 1 | • Ball bearing | |
| 21 | 907025 | 1 | • Lock washer | IK |
| 22 | 906635 | 1 | • Round nut | |
| 23 | 832632 | 1 | • Gear set | RATIO 2,15:1 |
| 23A | 948407 | X | • • Spring pin | |
| 24 | 914474 | 1 | • Lock ring | |
| 23 | 832725 | 1 | • Washer | |
| 28 | 953449 | 6 | • Stud | |
| 29 | 955825 | 6 | • Nut | |
| 30 | 925261 | 2 | • O-ring | IK |
| 31 | 875805 | 1 | • Zinc ring kit | (832524) |
| 32 | 940203 | 2 | • • Screw | |
| 33 | 897426 | 2 | • Sealing ring | IK |
| 34 | 839534 | 1 | • Line cutter | |
| 35 | | 1 | • PROPELLER CONE | REPLACED BY 850785, 851261. |
| | 850785 | 1 | • Propeller cone | |
| 35A | 851261 | 1 | • Washer | FOR PROPELLER WITH SHORT HUB, PZ 28015547- |
| 36 | 897367 | 1 | • Washer | |
| 37 | 804262 | 1 | • Plug | PZ-2785179 |
| | 839354 | 1 | • Plug | PZ2785180- |
| 38 | 804261 | 1 | • Gasket | PZ-2785179 |
| | 955974 | 1 | • O-ring | PZ2785180- |
| 40 | 944522 | X | • Shim | TH = 0,05 MM |
| | 42981 | X | • Shim | TH = 0,10 MM |
| | 42980 | X | • Shim | TH = 0,35 MM |
| 41 | 944970 | X | • Adjusting washer | TH = 1,60 MM |
| 42 | 944561 | X | • Adjusting washer | TH = 0,05 MM |
| | 944562 | X | • Adjusting washer | TH = 0,10 MM |
| | 851767 | X | • Adjusting washer | TH = 0,20 MM |
| 43 | 832191 | 1 | • Gasket | IK |
| 44 | 925256 | 1 | • O-ring | IK |
| 45 | 875183 | 1 | Splined sleeve | |
| 46 | 914508 | 1 | • Snap ring | |
| 47 | 941810 | 4 | Screw | |
| 48 | 853095 | 4 | Washer | |